



Einhell



Battery Charger

CE-BC 1 M

Item No.: 1002205

Ident No.: 11018

Bar Code: 4006825640298

The Einhell CE-BC 1 M battery charger is an intelligent universal battery charger with a microprocessor controller for gel, AGM, zero & low maintenance lead-acid batteries. The multi-stage charging cycle is controlled and monitored by a microprocessor controller, and charging is optimized to contribute to an extended battery life. Changing between 6 V and 12 V vehicle batteries is selected by pushbutton and it is suitable for vehicles which are not used for extended periods: The trickle charge function constantly maintains the optimal charge. Featuring type IP65 protection, the charger has electronic protection against overcharging, short-circuit and swapped poles. The clamps are fully insulated.



Features & Benefits

- Intelligent battery charger with microprocessor controller
- Multi-stage charging cycle, controlled/monitored by microprocessor
- Universal battery charger for various battery types
- For gel, AGM, zero and low maintenance lead-acid batteries
- Pushbutton for selecting between 6/12V vehicles
- Protection class IP65: Dustproof and protected against water jets
- Trickle charge function for a continuously ideal charge status
- For vehicles with long idle times (convertibles/motorcycles)
- Charging provides extended battery life
- El. protection against overcharging, short-circuit, swapped poles
- Fully insulated battery clamps
- Suspension eyelet for mounting to the wall



Technical Data

- Mains supply 220-240 V | 50 Hz
- Charging voltage 6 V / 12V
- Suitable for batteries (from min. Ah to max. Ah): 3-32 Ah
- Charging current Min. (arith./eff.) - Max. 1 / [-] A (arith./eff.) on 6 V d.c.
- Charging current Min. (arith./eff.) - Max. 1 / [-] A (arith./eff.) on 12 V d.c.



Logistic Data

- Product weight 0.22
- Gross weight single packaging 0.38
- Dimensions single packaging 152 x 66 x 233 mm
- Pieces per export carton 14 Pieces
- Gross weight export carton 5.8 kg
- Dimensions export carton 315 x 470 x 250 mm
- Container quantity (20"/40"/40"HC) 9702 | 21168 | 23520

