



Einhell

CAR EXPERT**Battery Charger****CE-BC 5 M LiFePO4****Item No.: 1002251**

Ident No.: 21024

Bar Code: 4006825671520

The Einhell battery charger CE-BC 5 M LiFePO4 is a smart system with multi-stage charging cycle, monitored by a microprocessor controller and suitable for all common 12 V vehicle batteries, especially for lithium iron phosphate batteries. The maintenance charging function protects the battery and extends its service life. The recondition mode and the force function allow deeply discharged batteries to be regenerated or revived. Overcharging, short-circuit and reverse polarity protection as well as the dust-tight and jet-water-protected housing ensure safety. The LCD battery voltage and charging progress indicator shows the status of the battery.

Features & Benefits



- Intelligent battery charger with microprocessor control
- Allround battery charger for various battery types
- For gel, AGM, maintenance-free lead-acid batteries
- Especially suitable for lithium-iron-phosphate batteries
- IP65 protection: dustproof and protected against water jets
- Trickle charge function for a permanently ideal state of charge
- Power supply mode for use as a power source
- LCD battery voltage and charge progress display
- Electronic overload, short circuit & reverse polarity protection
- Fully isolated battery clamps
- Suspension eyelets for wall-mounting

Technical Data

- Mains supply 220-240 V | 50 Hz
- Jump start no
- Charging voltage 12V
- Suitable for batteries (from min. Ah to max. Ah): 2-120 Ah
- Charging current Min. (arith./eff.) - Max. 5 / [-] A (arith./eff.) on 12 V d.c.
- Charging current (arith./eff.) at normal load on 12 V d.c. 5 A
- Charging current (arith./eff.) at automatic load on 12 V d.c. 5 A

Logistic Data

- Product weight 0.64
- Gross weight single packaging 0.87
- Dimensions single packaging 150 x 75 x 300 mm
- Pieces per export carton 10 Pieces
- Gross weight export carton 8.8 kg
- Dimensions export carton 390 x 315 x 320 mm
- Container quantity (20"/40"/40"HC) 7140 | 15540 | 17760

**MICROPROCESSOR-CONTROLLED****INCL. LiFe PO4 MODE****INCL. TRICKLE CHARGING MODE****12 V
2 - 120 Ah****ACCU
PB, CA/CA,
EFB, GEL, AGM
12 V****5 AMP.
MAX.**